

MTB

Multi-function ToolBox

- Firmware download, Coin Changer (Recycler) operational setting, IrDA download/ reading audit data, and sensor calibration.
- High convenience: storage several firmwares at one time.
- Chargeable battery and power saving design.
- Large screen to show information.
- Built-in memory and Micro-SD Card slot for large data storage.
- One multi-purpose cable for different ICT products.
- Friendly user interface.
- Easy to carry.



The logo for ICT, featuring the letters 'iCT' in a stylized blue font with a red dot above the 'i'.

Multi-function ToolBox

MTB (Multi-function ToolBox) is a total solution for ICT product maintenance. The portable programmer-MTB, presents data in a large LCM makes product maintenance easily and fast. MTB is high convenience that could storage several firmwares at the same time. Powerful multi functions include programmer, changer operation, IrDA download / reading audit data and sensor calibration. All-in-one design meets all requirements form market.

Specifications



Download Programmer

Bill Acceptor:

A / V Series, PA7, E77, Envy Series, NBA, L Series, PL77, LV77 Series, NK Series, P Series, S Series, XBA, TAO Light, BS7, X7P, NBA
Lockable Stacker Series (V7E, LX7, V77E, TAO-A/V, S7ER)

Coin Changer (Recycler):

CC6000, CC6100

CA:

UCA, SCA

Others:

GP58 CR/CA, Mini hopper, CVD, CSD



Power/Battery Information

Power supply from the embedded rechargeable Li-ion battery.

Power saving design for extended battery sustainability.

Battery charging through PC(USB port) or external adapter (DC 5V, 500mA or above)

Capacity: 2100 mAh

Continue working time: up to 6 hrs

Charging time: 4hrs (Capacity 0%~100%)



Memory Device

Built-in memory (4M Byte)

Micro-SD Card slot for large data storage. (Up to 32 GB)



Power Consumption

Standby: 3.7V, 350mA, 1.30W

Operation: 3.7V, 370mA, 1.40W

Maximum: 3.7V, 2A, 7.40W



Dimension

(L×W×T)151.2×100.2×30.1mm/

(L×W×T)5.95×3.94×1.18 inch



Weight

Approx. 300g / 0.663 lbs



Environmental

Operating Temperature: -5°C~50°

Storage Temperature: -20°C~70°C


Operating Humidity: 85%RH
(no condensation)

Battery in charge Temperature:
0°C~45°C



Recommended Applications

Portable device



Specifications are subject to change without prior notice.



International Currency Technologies

No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan

Phone: +886-2-2793-1236

Fax: +886-2-2793-6125

Email: sales@ictgroup.com.tw (Product Information)

fae@ictgroup.com.tw (Technical Service)

Website: www.ictgroup.com.tw